



746 Check'n'Roll™ 3 mm



- Ideal flooring for factory and warehouse premises or any kind of industrial applications to protect floors and materials.
- Withstands diluted acids and alkalis.
- Matting with excellent wear and tear resistance. Used as flooring, shelf liners and in all kinds of industrial applications in workshops, near machines and any place where objects may tend to slide on workbenches, carts, cars or lorry booths.



746 Check'n'Roll™ 3 mm

PRODUCT SPECIFICATIONS			
Designation	Non-directional matting		
Type	Flooring / runner		
Description	Industrial checker plate profile surface		
Material	Synthetic rubber		
Process	Calendering		
Category	Non-directional pattern		
Recommended use	Factory and warehouse premises or any kind of industrial applications to protect floors and materials.		
Colours	Black, Grey		
Weight	51.6 kg per mat		
Thickness	3 mm		
Standard sizes	140 cm x 10 m		
Custom sizes	Per liniair meter		
Special remarks	Black : resistance to temperature : -30°C, +70°C Grey : resistance to temperature : -20°C, +70°C		
PRODUCT TESTING			
Tests		Norms	Results
Compression deflection		U.S.	
	1.4 kg/cm²		
	2.8 kg/cm²		
Foam battery		ASTM D3574	
Abrasion resistance		ASTM D3884-01	
	500 Cycles		
	5000 Cycles		300 - 500 mm³
Static coefficient of friction		ASTM C1028-96	
Elongation		ASTM D412	200% ≤ 350%
Breaking load		ASTM D412	
Tear strength		ASTM D 1004	Black: 4 N/mm² Grey: 5 N/mm²
Hardness		DIN 53505	70 Shore A
Anti-slip		DIN 51130 and BG-RULE BGR181	
FIRE TESTING			
	Critical radiant flux	ASTM E-648	
	Fire retardancy	DIN4102	
		EN 13501-1	
	Flammability test	ASTM D2859	
ESD		ANSI ESD S7.1 50% Humidity	
Sustainability		<ul style="list-style-type: none">• Recyclable material• Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals)	